## **CLAIMS**

## What is claimed is:

5

10

15

20

25

1. An adjustable binding-fixative-massaging device for condoms—an integral binding-fixative-massaging device from soft and resilient material, comprises a pipe-shaped body and a vibration-transmitting device to be fixed/installed inside which, at the center of the pipe-shaped body a proper protrusion and several soft protrusions in extension are provided, further around and by two sides of said protrusion being provided plural soft massage protrusions, and at the central hole of the pipe-shaped body there is a vibration-transmitting device; and of the said pipe-shaped body one end being provided with a fastener strip in extension and the other end a fastener bead blocker with a fastener hole at its center, in which near the end of said fastener strip there are several semi-spherical fastener beads stringed together with spaces in between and at this end of the fastener strip is provided one cone-shaped fastener bead for inserting into the fastener hole of the fastener bead blocker; further a vibration-transmitting device, mainly a spring strip with one end bent into a contact strip for butting to the outer edge of the transmitting body and the other end bent upward to form a movable conducting strip behind the battery of the transmitting body, still one end of the vibration-transmitting device is provided with a bulging hole for a spin rod with spinning knob and bulging pins on different sites on said spin rod, to be inserted and spun;

through the above structures to pierce/butt the fastener strip at one end of the pipe-shaped body into the fastener hole of the fastener bead blocker at the other end of the pipe-shaped body to adjust a proper binding tightness and bind/fix the whole binding-fixative-massaging device at the root of a penis, and make or break with the spinning knob of the vibration-transmitting device to drive the movable conducting strip of the inner spring strip into or out of contact with the battery, to start or shut off

the vibration-transmitting device.